

Switch Solution

NS(M)-205PSE Series
NS(M)-208PSE Series
NS(M)-205PF Series

tNS-200SP
tNS-200IN



MSM-6226(G)

MSM-508 Series



NS-208-IP67

NS-205-IP67



NS-200 Series

PoE

Management

IP67
Water-Proof

Media
Converter

Ring
Redundancy

Fiber

EN50155
Certification
(M12 Connector)

Standard

- Guaranteed performance over the full wide range operating temperature (-40°C~+75°C)
- DIN-Rail mount for industrial usage
- 0% packet loss per port / 60 sec
- IP67 grade protection approval (Rugged RJ45 Connector for anti-vibration and shock)
- Support Modbus protocol for integration
- Redundant Power Inputs
- Built-in Cyber-Ring redundant technology
- EN50155-certified for harsh railway standards
- Support PoE (Power Over Ethernet), provide power input +24V or +48V

RSM-40X Series

RS-40X Series



RS(M)-405F Series
NS(M)-205PF Series
NS(M)-206AF Series
NS(M)-209F Series



NSM-208-M12



NS-208R



NSM-208PSE-M12



NS-2XX Series
NSM-2XX Series



ICP DAS CO., LTD.

<http://www.icpdas.com>

TEL : +886-3-597-3366

FAX : +886-3-597-3733

e-mail : sales@icpdas.com