

Switch Solution

Media Converter

IP67 Water-Proof

Management

PoE

Standard

EN50155 Certification (M12 Connector)

Ring Redundancy

Fiber

RSM-40X Series

- Guaranteed performance over the full wide range operating temperature (-40°C~+75°C)
- DIN-Rail mount for industrial usage
- 0% packet loss per port / 60 sec
- IP67 grade protection approval (Rugged RJ45 Connector for anti-vibration and shock)
- Support Modbus protocol for integration
- Redundant Power Inputs
- Built-in Cyber-Ring redundant technology
- EN50155-certified for harsh railway standards
- Support PoE (Power Over Ethernet), provide power input +24V or +48V



tNS-200SP
tNS-200IN

NS(M)-205PSE Series
NS(M)-208PSE Series
NS(M)-205PF Series

RS-40X Series



PoE

Ring Redundancy



MSM-508 Series

MSM-6226(G)



NS-205-IP67



NS-208-IP67

Management

Fiber



RS(M)-405F Series
NS(M)-205PF Series
NS(M)-206AF Series
NS(M)-209F Series

NSM-208PSE-M12



NSM-208-M12

NS-208R



IP67 Water-Proof

EN50155 Certification (M12 Connector)



NS-200 Series

Media Converter

Standard



NS-2XX Series
NSM-2XX Series



ICP DAS CO., LTD.

TEL : +886-3-597-3366

FAX : +886-3-597-3733

e-mail : sales@icpdas.com

<http://www.icpdas.com>